## NSN 5950-00-460-1088

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-460-1088
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.297 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.859 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
3.190 inches
Body Width:
3.060 inches
Body Height:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
200.0 milliamperes ac single component 1st secondary
Winding Operating Voltage:
6.00 ac volts single component 1st secondary and 14.00 ac volts single component 1st secondary and 54.00 ac volts single component 1st
secondary and 58.00 ac volts single component 1st secondary and 64.00 ac volts single component 1st secondary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
14 pin
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-00-460-1088

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0