

View Online at <https://aerobasegroup.com/nsn/5950-00-461-2485>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group3.500 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

3.500 inches 3.500 inches

Body Outside Diameter:

4.250 inches 4.250 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

85.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

46.00 ac volts single component 3rd secondary16.25 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0