NSN 5950-00-461-3956

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-461-3956

Reliability Indicator:
Not established
Turn Quantity:
7000 single component single winding
Mounting Hole Diameter:
0.188 inches single group
Frequency Rating:
60.0 hertz single component
Body Length:
2.186 inches
Body Width:
1.726 inches
Body Height:
0.990 inches
Distance Between Mounting Facility Centers:
1.938 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
2 single group
2 single group Mounting Method:
2 single group Mounting Method: Flange single group and unthreaded hole single group
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method:
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size:
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage:
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding Terminal Type And Quantity:
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life:
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00500 inches american wire gage single component single winding Winding Operating Voltage: 110.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: