

View Online at <https://aerobasegroup.com/nsn/5950-00-462-2877>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Overall Height:

Between 4.750 inches and 4.750 inches and 5.000 inches 5.000 inches

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Delta-wyedelta-wye

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

5.750 inches 5.750 inches

Body Width:

4.450 inches 4.450 inches

Maximum Operating Temp:

100.0 degrees celsius100.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

3 primary single component and 3 primary single component and 2 secondary single component2 secondary single component

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

14.9 amperes ac single component all secondary

Winding Operating Voltage:

204.00 ac volts single component all primary and 22.00 ac volts single component all secondary213.00 ac volts single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 turret and 6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0