

View Online at <https://aerobasegroup.com/nsn/5950-00-462-5832>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

2.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.985 inches single mounting facility single center group and 2.015 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.090 inches single mounting facility single center group and 1.180 inches single mounting facility single center group

Overall Height:

2.690 inches

Overall Width:

2.120 inches

Frequency Rating:

380.0 hertz single component and 1000.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded and brought out to terminal single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

55.0 milliamperes ac single component 1st secondary

Winding Power Rating:

62.4 volts-amperes single component 2nd secondary 16.9 volts-amperes single component 1st secondary

Winding Operating Voltage:

308.50 ac volts single component 1st secondary 115.00 ac volts single component single primary 480.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0