## NSN 5950-00-463-9662

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-463-9662

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 4.062 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.312 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Length: 4.062 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width:
4.062 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width:
Center To Center Distance Between Mounting Facilities Parallel To Width:
-
3.312 inches sindle mounting facility single center droup
Frequency Rating:
45.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
5.062 inches
Body Width:
4.312 inches
Body Height:
5.500 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 7 secondary single component
Thready Qty Per Inch (tpi):
20 single group
Thread Size:
0.250 inches single group
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
20 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0