

View Online at <https://aerobasegroup.com/nsn/5950-00-464-2511>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.685 inches 2nd mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.850 inches 2nd mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.320 inches

Body Width:

2.540 inches

Body Height:

4.820 inches

Distance Between Mounting Facility Centers:

1.850 inches 1st mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 2nd group 2 1st group

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches all groupings

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary 27.40 ac volts single component single secondary and 197.00 ac volts single component single secondary

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

24 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0