

View Online at <https://aerobasegroup.com/nsn/5950-00-465-2310>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single componentthree phase to three phase single component

**Transformer Winding Connection Type:**

Delta-wyedelta-wye

**Body Length:**

3.500 inches 3.500 inches

**Body Width:**

2.500 inches 2.500 inches

**Body Height:**

2.000 inches 2.000 inches

**Maximum Operating Temp:**

120.0 degrees celsius120.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

286.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

35.00 ac volts single component single secondary480.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0