## NSN 5950-00-465-2310

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-465-2310

#### **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

#### Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-wyedelta-wye

#### **Body Length:**

3.500 inches 3.500 inches

#### **Body Width:**

2.500 inches 2.500 inches

#### **Body Height:**

2.000 inches 2.000 inches

#### **Maximum Operating Temp:**

120.0 degrees celsius120.0 degrees celsius

## Inclosure Type:

Fully enclosedfully enclosed

#### **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Threaded hole single groupthreaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

## Thread Size:

0.138 inches single group

## **Winding Operating Current:**

286.0 milliamperes ac single component single secondary

#### **Winding Operating Voltage:**

35.00 ac volts single component single secondary480.00 ac volts single component single primary

#### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

7 threaded stud

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-00-465-2310

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0