

View Online at <https://aerobasegroup.com/nsn/5950-00-465-2313>

Reliability Indicator:

Not establishednot established

Overall Length:

3.938 inches 3.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

Overall Height:

6.125 inches 6.125 inches

Overall Width:

3.375 inches 3.375 inches

Frequency Rating:

47.5 hertz single component and 47.5 hertz single component and 63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

12.0 amperes ac single component single secondary

Winding Power Rating:

110.4 volts-amperes single component single secondary

Winding Operating Voltage:

9.20 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0