

View Online at <https://aerobasegroup.com/nsn/5950-00-465-8290>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.748 inches single mounting facility single center group and 1.752 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.310 inches single mounting facility single center group and 1.314 inches single mounting facility single center group

Overall Height:

1.875 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.750 inches

Body Width:

2.380 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

310.0 milliamperes dc single component 4th secondary

Winding Power Rating:

41.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

34.20 dc volts single component 1st secondary

Special Features:

One primary winding and five secondary windings

Test Data Document:

37695-328720 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

19 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0