## NSN 5950-00-465-9702

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-465-9702

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

### **Overall Height:**

2.719 inches

### **Frequency Rating:**

380.0 hertz single component and 420.0 hertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

### **Winding Shielding Method:**

Internal shield brought out to terminal single component

### **Body Length:**

1.938 inches

### **Body Width:**

1.812 inches

### **Body Height:**

2.438 inches

### **Maximum Operating Temp:**

96.0 degrees celsius

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

#### **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

750.0 milliamperes ac single component 2nd secondary

### **Winding Operating Voltage:**

32.00 ac volts single component 2nd secondary21.00 ac volts single component 1st secondary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

11 tab, solder lug

# NSN 5950-00-465-9702

Power Transformer - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0