

View Online at <https://aerobasegroup.com/nsn/5950-00-465-9703>

Reliability Indicator:

Not establishednot established

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

1.312 inches 1.312 inches

Body Width:

1.312 inches 1.312 inches

Body Height:

1.750 inches 1.750 inches

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

50.0 milliamperes ac single component single primary

Winding Operating Voltage:

37.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0