

View Online at <https://aerobasegroup.com/nsn/5950-00-466-1622>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.250 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.250 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Body Length:**

2.000 inches

**Body Outside Diameter:**

2.875 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Winding Power Rating:**

250.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

35.00 ac volts single component single secondary 115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

5 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0