NSN 5950-00-466-9817

Pulse Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-466-9817

| view Online at https://defobasegroup.com/nsi//0330-00-400-3017 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group |
| Frequency Rating: |
| 10.0 kilohertz single component |
| Body Length: |
| 1.380 inches |
| Body Width: |
| 1.380 inches |
| Body Height: |
| 1.000 inches |
| Maximum Operating Temp: |
| 105.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thread Size: |
| 0.112 inches single group |
| Winding Operating Current: |
| 70.7 amperes ac single component 1st secondary |
| Dc Resistance Rating In Ohms: |
| 1.400 single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 7 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0