

View Online at <https://aerobasegroup.com/nsn/5950-00-467-1592>

Reliability Indicator:

Not establishednot established

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

3.000 inches 3.000 inches

Body Width:

1.750 inches 1.750 inches

Body Height:

2.430 inches 2.430 inches

Distance Between Mounting Facility Centers:

2.375 inches single mounting facility single center group2.375 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Voltage:

120.00 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0