

View Online at <https://aerobasegroup.com/nsn/5950-00-467-1855>

**Reliability Indicator:**

Not establishednot establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single componentinternal shield grounded to core single component

**Body Length:**

3.562 inches 3.562 inches 3.562 inches

**Body Width:**

3.062 inches 3.062 inches 3.062 inches

**Body Height:**

4.875 inches 4.875 inches 4.875 inches

**Maximum Operating Temp:**

105.0 degrees celsius105.0 degrees celsius105.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

20.0 amperes ac single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary5.50 ac volts single component single secondary5.50 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

2 tab, solder lug and 2 turret

**Shelf Life:**

**Demilitarization:**

No

**Fig:**

A058b0