

View Online at <https://aerobasegroup.com/nsn/5950-00-467-1855>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

3.562 inches 3.562 inches 3.562 inches

Body Width:

3.062 inches 3.062 inches 3.062 inches

Body Height:

4.875 inches 4.875 inches 4.875 inches

Maximum Operating Temp:

105.0 degrees celsius105.0 degrees celsius105.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary5.50 ac volts single component single secondary5.50 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 tab, solder lug and 2 turret

Shelf Life:

Demilitarization:

No

Fig:

A058b0