NSN 5950-00-469-3901

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-469-3901

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.718 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.625 inches single mounting facility single center group
Overall Height:
2.380 inches
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.340 inches
Body Width:
2.280 inches
Body Height:
2.130 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
1.5 amperes dc single component single secondary
pgggg
Winding Operating Voltage:
Winding Operating Voltage:
Winding Operating Voltage: 25.20 ac volts single component single secondary115.00 ac volts single component single primary
Winding Operating Voltage: 25.20 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator:
Winding Operating Voltage: 25.20 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group
Winding Operating Voltage: 25.20 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity:
Winding Operating Voltage: 25.20 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret

--

NSN 5950-00-469-3901

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0