

View Online at <https://aerobasegroup.com/nsn/5950-00-470-0112>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

4.271 inches 4.271 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches single mounting facility single center group3.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single componentthree phase to three phase single component

**Transformer Winding Connection Type:**

Delta-deltadelta-delta

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single component

**Body Length:**

3.891 inches 3.891 inches

**Body Width:**

3.016 inches 3.016 inches

**Body Height:**

2.016 inches 2.016 inches

**Maximum Operating Temp:**

85.0 degrees celsius85.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

500.0 milliamperes dc single component 2nd secondary

**Winding Operating Voltage:**

4.20 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0