NSN 5950-00-470-5074

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-470-5074

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

2.750 inches 2.750 inches

Body Width:

2.375 inches 2.375 inches

Body Height:

3.812 inches 3.812 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Voltage:

64.00 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

NSN 5950-00-470-5074

Power Transformer - Page 2 of 2



Fiig:

A058b0