

View Online at <https://aerobasegroup.com/nsn/5950-00-471-4567>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.440 inches single mounting facility single center group and 4.560 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.219 inches single mounting facility single center group and 6.281 inches single mounting facility single center group

**Mounting Slot Width:**

0.290 inches single group and 0.330 inches single group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

7.000 inches

**Body Width:**

7.000 inches

**Body Height:**

8.000 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

160.0 amperes ac single component single secondary

**Winding Power Rating:**

1.072 kilovolt-amperes single component single secondary

**Winding Operating Voltage:**

6.70 ac volts single component single secondary

**Test Data Document:**

14304-6049-5102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0