

View Online at <https://aerobasegroup.com/nsn/5950-00-471-4567>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.440 inches single mounting facility single center group and 4.560 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.219 inches single mounting facility single center group and 6.281 inches single mounting facility single center group

Mounting Slot Width:

0.290 inches single group and 0.330 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

7.000 inches

Body Width:

7.000 inches

Body Height:

8.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

160.0 amperes ac single component single secondary

Winding Power Rating:

1.072 kilovolt-amperes single component single secondary

Winding Operating Voltage:

6.70 ac volts single component single secondary

Test Data Document:

14304-6049-5102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0