

View Online at <https://aerobasegroup.com/nsn/5950-00-472-3590>

**Reliability Indicator:**

Not establishednot establishednot establishednot established

**Overall Length:**

Between 2.032 inches and 2.032 inches and 2.032 inches and 2.032 inches and 2.094 inches 2.094 inches 2.094 inches 2.094 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.484 inches single mounting facility single center group and 1.484 inches single mounting facility single center group and 1.484 inches single mounting facility single center group and 1.484 inches single mounting facility single center group and 1.516 inches single mounting facility single center group1.516 inches single mounting facility single center group1.516 inches single mounting facility single center group1.516 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.234 inches single mounting facility single center group and 1.234 inches single mounting facility single center group and 1.234 inches single mounting facility single center group and 1.234 inches single mounting facility single center group and 1.266 inches single mounting facility single center group1.266 inches single mounting facility single center group1.266 inches single mounting facility single center group1.266 inches single mounting facility single center group

**Overall Height:**

Between 3.001 inches and 3.001 inches and 3.001 inches and 3.001 inches and 3.249 inches 3.249 inches 3.249 inches 3.249 inches

**Overall Width:**

Between 1.719 inches and 1.719 inches and 1.719 inches and 1.719 inches and 1.781 inches 1.781 inches 1.781 inches 1.781 inches

**Frequency Rating:**

50.0 hertz single component and 50.0 hertz single component and 50.0 hertz single component and 50.0 hertz single component and 440.0 hertz single component440.0 hertz single component440.0 hertz single component440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

**Maximum Transformer Power Rating:**

10.0 volt-ampere single component10.0 volt-ampere single component10.0 volt-ampere single component10.0 volt-ampere single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single componentinternal shield grounded to core single componentinternal shield grounded to core single component

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Hermetically sealedhermetically sealedhermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single groupthreaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component1 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

640.0 milliamperes ac single component single secondary

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0