

View Online at <https://aerobasegroup.com/nsn/5950-00-472-3957>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches single mounting facility single center group2.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.188 inches single mounting facility single center group1.188 inches single mounting facility single center group

**Overall Height:**

2.719 inches 2.719 inches

**Frequency Rating:**

55.0 hertz single component and 55.0 hertz single component and 65.0 hertz single component65.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

3.062 inches 3.062 inches

**Body Width:**

2.500 inches 2.500 inches

**Body Height:**

4.250 inches 4.250 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

35.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

6.30 ac volts single component 1st secondary115.00 ac volts single component single primary480.00 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 standoff insulator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0