

View Online at <https://aerobasegroup.com/nsn/5950-00-473-1841>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.250 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.875 inches

Body Width:

5.000 inches

Body Height:

7.750 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

250.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

730.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

200.00 ac volts single component single primary and 220.00 ac volts single component single primary and 240.00 ac volts single component single primary and 260.00 ac volts single component single primary

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0