

View Online at <https://aerobasegroup.com/nsn/5950-00-473-6063>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.516 inches single mounting facility single center group2.516 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.516 inches single mounting facility single center group2.516 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

**Body Length:**

3.130 inches 3.130 inches

**Body Width:**

3.130 inches 3.130 inches

**Body Height:**

0.363 inches 0.363 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

8 single group8 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

300.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

6.50 ac volts single component 1st secondary111.50 ac volts single component single primary and 115.00 ac volts single component single primary and 118.40 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

12 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0