

View Online at <https://aerobasegroup.com/nsn/5950-00-473-6063>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.516 inches single mounting facility single center group2.516 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.516 inches single mounting facility single center group2.516 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

3.130 inches 3.130 inches

Body Width:

3.130 inches 3.130 inches

Body Height:

0.363 inches 0.363 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

8 single group8 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

300.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.50 ac volts single component 1st secondary111.50 ac volts single component single primary and 115.00 ac volts single component single primary and 118.40 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0