

View Online at <https://aerobasegroup.com/nsn/5950-00-473-6065>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.125 inches single mounting facility single center group6.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.125 inches single mounting facility single center group4.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.375 inches single group0.375 inches single group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

7.750 inches 7.750 inches

Body Width:

5.625 inches 5.625 inches

Body Height:

7.750 inches 7.750 inches

Inclosure Type:

Partially enclosed, double shellpartially enclosed, double shell

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Voltage:

105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0