

View Online at <https://aerobasegroup.com/nsn/5950-00-473-6065>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.125 inches single mounting facility single center group6.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.125 inches single mounting facility single center group4.125 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.375 inches single group0.375 inches single group

**Frequency Rating:**

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single component

**Body Length:**

7.750 inches 7.750 inches

**Body Width:**

5.625 inches 5.625 inches

**Body Height:**

7.750 inches 7.750 inches

**Inclosure Type:**

Partially enclosed, double shellpartially enclosed, double shell

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Winding Operating Voltage:**

105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary

**Terminal Type And Quantity:**

6 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0