

View Online at <https://aerobasegroup.com/nsn/5950-00-474-3187>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.750 inches single mounting facility single center group

**Frequency Rating:**

47.5 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

5.620 inches

**Body Width:**

4.620 inches

**Body Height:**

5.620 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Special Features:**

Xcase metal material; primary winding rated 104 to 126 v; secondary windings rated 6.1 v at 1.05 amp, 6.5 v at 25 amp, 136 v at 120 ma w/center tap, 150 v at 100 ma w/center tap, 680 v at 400 ma w/center tap, 1.35 kv at 5 ma w/center tap

**Terminal Type And Quantity:**

18 banana plug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0