

View Online at <https://aerobasegroup.com/nsn/5950-00-474-3187>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.750 inches single mounting facility single center group

Frequency Rating:

47.5 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.620 inches

Body Width:

4.620 inches

Body Height:

5.620 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Special Features:

Xcase metal material; primary winding rated 104 to 126 v; secondary windings rated 6.1 v at 1.05 amp, 6.5 v at 25 amp, 136 v at 120 ma w/center tap, 150 v at 100 ma w/center tap, 680 v at 400 ma w/center tap, 1.35 kv at 5 ma w/center tap

Terminal Type And Quantity:

18 banana plug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0