

View Online at <https://aerobasegroup.com/nsn/5950-00-476-5596>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.625 inches single mounting facility single center group4.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 47.0 hertz single component and 63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

5.250 inches 5.250 inches

Body Width:

3.438 inches 3.438 inches

Body Height:

1.453 inches 1.453 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

6 single group6 single group

Mounting Method:

Unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

800.0 milliamperes ac single component single secondary

Winding Operating Voltage:

56.00 ac volts single component single secondary

Terminal Type And Quantity:

7 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0