

View Online at <https://aerobasegroup.com/nsn/5950-00-476-8047>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

3.125 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

700.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

24.00 ac volts single component 3rd secondary 115.00 ac volts single component all primary 24.00 ac volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0