

View Online at <https://aerobasegroup.com/nsn/5950-00-477-6702>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.938 inches single mounting facility single center group1.938 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

Between 2.740 inches and 2.740 inches and 2.760 inches 2.760 inches

**Body Width:**

Between 2.550 inches and 2.550 inches and 2.570 inches 2.570 inches

**Body Height:**

Between 3.180 inches and 3.180 inches and 3.200 inches 3.200 inches

**Maximum Operating Temp:**

75.0 degrees celsius75.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

7.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

8.00 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

13 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0