

View Online at <https://aerobasegroup.com/nsn/5950-00-478-4219>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.304 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.178 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 500.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.250 inches

Body Width:

1.900 inches

Body Height:

1.000 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Voltage:

7.00 ac volts single component 3rd secondary 115.00 ac volts single component all primary 40.00 ac volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0