

View Online at <https://aerobasegroup.com/nsn/5950-00-481-0772>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.219 inches

Body Width:

1.719 inches

Body Height:

2.875 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

300.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

500.00 ac volts single component 1st secondary 25.50 ac volts single component 2nd secondary 86.50 ac volts single component single primary and 115.00 ac volts single component single primary

Special Features:

Center tap secondary terminal common to primary terminal no. One

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0