# NSN 5950-00-482-1428

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-482-1428

### **Reliability Indicator:**

Not establishednot established

### **Overall Length:**

Between 2.295 inches and 2.295 inches and 2.325 inches 2.325 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.795 inches single mounting facility single center group and 1.795 inches single mounting facility single center group and 1.825 inches

single mounting facility single center group1.825 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.005 inches single mounting facility single center group and 1.005 inches single mounting facility single center group and 1.035 inches

single mounting facility single center group1.035 inches single mounting facility single center group

## **Overall Height:**

Between 1.735 inches and 1.735 inches and 1.765 inches 1.765 inches

#### **Overall Width:**

Between 1.675 inches and 1.675 inches and 1.735 inches 1.735 inches

#### Mounting Hole Diameter:

0.164 inches single group and 0.164 inches single group and 0.174 inches single group0.174 inches single group

#### **Frequency Rating:**

400.0 hertz single component400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

# Maximum Transformer Power Rating:

80.0 volt-ampere single component80.0 volt-ampere single component

### Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

#### Inclosure Type:

Fully enclosedfully enclosed

### Mounting Facility Quantity:

2 single group2 single group

### **Mounting Method:**

Unthreaded hole single groupunthreaded hole single group

### Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

### Winding Operating Current:

4.0 amperes ac single component single secondary

### Winding Operating Voltage:

20.00 ac volts single component single secondary115.00 ac volts single component single primary

# Terminal Type And Quantity:

5 turret

## Shelf Life:

N/a

Unit Of Measure:

--

- Demilitarization:
- No

# NSN 5950-00-482-1428

Power Transformer - Page 2 of 2

**Fiig:** A058b0

