

View Online at <https://aerobasegroup.com/nsn/5950-00-482-2940>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.250 inches single group

Frequency Rating:

600.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.750 inches

Body Width:

5.360 inches

Body Height:

5.810 inches

Distance Between Mounting Facility Centers:

6.000 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

0.226 milliamperes ac single component single secondary

Winding Power Rating:

256.0 watts single component single secondary

Winding Operating Voltage:

5.60 ac minor wet single component single primary

Special Features:

Reference data, ti-6310.23, fa 8200e, 1t7, pg 10-129, vol 2, sec 10-11/ti-6310.41, fa 8200f, 1t7, pg 10-129, vol 2, sec 10-11/ti-6310.4a, fa 8200, 1t7, pg 10-101, vol 2, sec 10-11

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0