NSN 5950-00-482-2940

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-482-2940
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.250 inches single group
Frequency Rating:
600.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
6.750 inches
Body Width:
5.360 inches
Body Height:
5.810 inches
Distance Between Mounting Facility Centers:
6.000 inches single mounting facility single center group
Inclosure Type:
Hermetically sealed with oil
Mounting Facility Quantity:
2 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
0.226 milliamperes ac single component single secondary
Winding Power Rating:
256.0 watts single component single secondary
Winding Operating Voltage:
5.60 ac minor wet single component single primary
Special Features:
Reference data, ti-6310.23, fa 8200e, 1t7, pg 10-129, vol 2, sec 10-11/ti-6310.41, fa 8200f, 1t7, pg 10-129, vol 2, sec
10-11/ti-6310.4a, fa 8200, 1t7, pg 10-101, vol 2, sec 10-11
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:

Nic

Demilitarization:

NSN 5950-00-482-2940

Power Transformer - Page 2 of 2



Fiig:

A058b0