

View Online at <https://aerobasegroup.com/nsn/5950-00-483-4009>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 1.563 inches and 1.625 inches

Body Width:

Between 1.563 inches and 1.625 inches

Body Height:

Between 2.250 inches and 2.500 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

900.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

27.0 volts-amperes single component 2nd secondary 17.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

30.00 ac volts single component 2nd secondary 15.00 ac volts single component 1st secondary

Test Data Document:

36452-10779 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0