NSN 5950-00-484-3113

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-484-3113

| | ility Indicator: tablished |
|---------|--|
| | r To Center Distance Between Mounting Facilities Parallel To Length: |
| | nches single mounting facility single center group |
| | r To Center Distance Between Mounting Facilities Parallel To Width: |
| | nches single mounting facility single center group |
| | ency Rating: |
| • | ertz single component and 400.0 hertz single component |
| | output Phase Relationship: |
| - | phase to three phase single component |
| | ng Shielding Method: |
| | I shield grounded to core single component |
| | Length: |
| 2.940 i | - |
| | Width: |
| 2.500 i | |
| | Height: |
| 1.690 i | • |
| | ure Type: |
| | nclosed |
| - | ing Facility Quantity: |
| | e group |
| - | ing Method: |
| | led hole single group |
| Windir | ng Function And Quantity: |
| 1 prima | ary single component and 1 secondary single component |
| Thread | dy Qty Per Inch (tpi): |
| 32 sinç | gle group |
| Thread | d Size: |
| 0.138 i | nches single group |
| Windir | ng Operating Voltage: |
| 115.00 | ac volts single component single primary |
| Thread | d Series Designator: |
| Unc sir | ngle group |
| Termir | nal Type And Quantity: |
| 7 tab, | solder lug |
| Shelf I | Life: |
| N/a | |
| Unit O | f Measure: |
| | |
| Demili | tarization: |
| No | |

NSN 5950-00-484-3113

Power Transformer - Page 2 of 2

Fiig: A058b0

