## NSN 5950-00-485-3291

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-485-3291

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.297 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.859 inches single mounting facility single center group                 |
| Inductance Type:  |
| Fixed   |
| Inductance Rating:  |
| 300.00 millihenries single component single winding                       |
| Body Length:  |
| 3.062 inches  |
| Body Width:   |
| 2.625 inches  |
| Body Height:  |
| 3.188 inches  |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Rating Method:  |
| Electrical single component single winding                                |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.164 inches single group   |
| Winding Operating Current:  |
| 800.0 milliamperes dc single component single winding                     |
| Dc Resistance Rating In Ohms:   |
| 2.250 single component single winding                                     |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 2 standoff, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5950-00-485-3291

Reactor - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A058b0