

View Online at <https://aerobasegroup.com/nsn/5950-00-486-0078>

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.984 inches single mounting facility single center group and 4.016 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.984 inches single mounting facility single center group and 2.016 inches single mounting facility single center group

Overall Height:

6.620 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 4.940 inches and 5.000 inches

Body Width:

Between 2.940 inches and 3.000 inches

Body Height:

Between 5.940 inches and 6.000 inches

Maximum Operating Temp:

122.0 degrees fahrenheit

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Power Rating:

175.0 volts-amperes single component single primary

Special Test Features:

Navord od41152

Test Data Document:

08241-8460-3011 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 solder stud

Reference Number Differentiating Characteristics:

As differentiated by special test features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0