

View Online at <https://aerobasegroup.com/nsn/5950-00-486-9504>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.859 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.297 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

3.062 inches

Body Width:

2.625 inches

Body Height:

3.188 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

1.4 amperes ac single component all secondary

Winding Operating Voltage:

8.00 ac volts single component 1st secondary 27.00 ac volts single component 3rd secondary 110.00 ac volts single component single primary and 115.00 ac volts single component single primary and 120.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0