

View Online at <https://aerobasegroup.com/nsn/5950-00-487-8144>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.750 inches single mounting facility single center group3.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.500 inches single mounting facility single center group3.500 inches single mounting facility single center group

**Frequency Rating:**

420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Maximum Transformer Power Rating:**

16.0 decibels single component16.0 decibels single component

**Body Length:**

5.500 inches 5.500 inches

**Body Width:**

4.500 inches 4.500 inches

**Body Height:**

6.750 inches 6.750 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

7.0 amperes ac single component single primary

**Winding Operating Voltage:**

50.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0