

View Online at <https://aerobasegroup.com/nsn/5950-00-488-3002>

Reliability Indicator:

Not establishednot established

Mounting Hole Diameter:

0.146 inches single group and 0.146 inches single group and 0.166 inches single group0.166 inches single group

Frequency Rating:

4.0 kilohertz single component4.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

Between 2.320 inches and 2.320 inches and 2.380 inches 2.380 inches

Body Width:

Between 0.970 inches and 0.970 inches and 1.030 inches 1.030 inches

Body Height:

Between 0.970 inches and 0.970 inches and 1.030 inches 1.030 inches

Maximum Operating Temp:

185.0 degrees celsius185.0 degrees celsius

Distance Between Mounting Facility Centers:

1.570 inches single mounting facility single center group and 1.570 inches single mounting facility single center group and 1.630 inches single mounting facility single center group1.630 inches single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

66.0 milliamperes ac single component single primary

Winding Operating Voltage:

2.00 ac volts single component single primary

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0