

View Online at <https://aerobasegroup.com/nsn/5950-00-488-9901>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.930 inches single mounting facility single center group2.930 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Mounting Slot Width:

0.234 inches single group0.234 inches single group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 1.0 kilohertz single component1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

5.620 inches 5.620 inches

Body Width:

3.500 inches 3.500 inches

Body Height:

4.250 inches 4.250 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Slot single groupslot single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 5 secondary single component5 secondary single component

Winding Operating Current:

375.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

22.00 dc volts single component 1st secondary

Special Features:

2primary windings; five secondary windings, also current and voltage on secondaries have been rectified

Terminal Type And Quantity:

17 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0