

View Online at <https://aerobasegroup.com/nsn/5950-00-489-1811>

Reliability Indicator:

Not establishednot established

Overall Length:

2.950 inches 2.950 inches

Frequency Rating:

10.0 kilohertz single component10.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

2.700 inches 2.700 inches

Body Width:

2.700 inches 2.700 inches

Body Height:

1.400 inches 1.400 inches

Distance Between Mounting Facility Centers:

2.285 inches single mounting facility single center group and 2.285 inches single mounting facility single center group and 2.315 inches single mounting facility single center group2.315 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thread Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

125.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

215.00 ac volts single component 2nd secondary1.057 ac kilovolts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0