

View Online at <https://aerobasegroup.com/nsn/5950-00-489-2099>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.190 inches single mounting facility single center group2.190 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

**Frequency Rating:**

45.0 hertz single component and 45.0 hertz single component and 440.0 hertz single component440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

2.810 inches 2.810 inches

**Body Width:**

2.380 inches 2.380 inches

**Body Height:**

2.880 inches 2.880 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

2.7 amperes dc single component 1st secondary

**Winding Operating Voltage:**

8.50 dc volts single component 1st secondary

**Special Features:**

All secondary voltage and current has been rectified

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

13 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0